





C6B Pro

6.5" PREMIUM BT CEILING SPEAKERS (PAIR)



Remote Control



Dedicated Presets



Combo Pack



Detachable Logo



Magnetic Grille



aptX Premium Audio

The T8 two-way IP65 loudspeakers with built-in 100V transformer and 16Ω power tap are perfect for both distributed and near-field applications in environments such as retail stores, restaurants, bar terrace, churches, malls or conferences. The speakers are housed in a stylish weather proof plastic cabinet (IP65 - using the back cover) providing an excellent architectural integration, both indoor and outdoor. The very accurate speaker's coverage allows the people, among the audience, to perceive the sound in the same way. The low frequencies are reproduced by a 8" direct-radiating woofer with a polypropylene cone, while the high-frequency section is based on a titanium tweeter. A U-bracket is included and will support your installation on the wall or ceiling.

Product Type

2-Way BT Premium Ceiling Speakers

RMS Power

60W

Amplifier Power

30W + 30W (C6B PRO Slave Speaker Output)

Wireless Range

>10m (32.8ft)

High Frequency Driver

0.75" Pivoting (±10°) Silk Dome Tweeter

Power Input

Power Supply: AC 100V - 240V | DC 24V- 2.5A Output

Grille

White Frameless Magnetic Grille (Paintable) | Detachable Logo

Cutout Diameter 209mm (8.2")

Fixation

Specially Designed Dog Legs Ceiling Fixation

Accessories

Black Frameless Magnetic Grille (not included)

Frequency Response (-6dB)

62Hz - 20kHz

Program Power

120W

DSP Presets

Classical | Vocal Enhance | Flat | Bass Enhance | Bass Cut | Treble Enhance | Treble Cut | Pop | Rock | Jazz

Maximum SPL (calculated)

107.8dB (2 Coupled Speakers)

Audio Signal Inputs

Stereo BT | Audio Line-in

Power Consumption

60W

IP Rating

Indoor Use

Mounting Depth

102mm (4")

Net Weight

Master - 1.5kg (3.3lb) | Slave - 1.5kg (3.3lb)

Nominal Coverage (-6dB)

100° Conical

Nominal Impedance

8Ω (C6B Pro Slave)

Wireless Connection System

BT v5.0 aptX LL

Low Frequency Driver

6.5" Polypropylene Cone Woofer

Input Connectors

1 x Stereo RCA (Master Speaker) | Gold Plated Binding Posts (Slave Speaker)

Special Features

Tool Free Install | Remote Control | 50% Level Limiter | Mono-Stereo Switch

Dimensions (ØxD)

234mm x 105mm (9.21" x 4.1")

Wall / Ceiling Thickness

7mm to 20mm (0.28" to 0.79")

Shipping Weight

4.5kg (9.9lb